



* Front grille and mounting bracket have been painted to match the ceiling

Key Features

- Larger cooling capacity
- Dual evaporator
- Ready for “Plug-and-Play” installation
- No ducting required
- Easy accessibility
- Standard and 24V thermostat options available

- Allows for maximum racking space
- Is virtually invisible in the cellar
- Includes a condensate pump system
- Grille of unit comes with a smooth, primed finish
- 55°F temperature differential
- Front grille and mounting bracket are paintable
- Built-in cold weather start kit on condensing unit

Specifications

Model	CM9000 Twin-S	CM9000 Twin-S (24V)
Cellar Size (cu. ft.)	Approx. 3000	
BTU/h (w/85°F air entering the condenser coil)	8500	
CFM	Evaporator: 308	Condenser: 1070
Dimensions	Evaporator: 12.75”H x 14.5”W x 35.75”D (x2) w/mounting bracket: 17.10”H x 38.75”D (x2)	Condenser: 16.6”H x 18.98”W x 24”D
Refrigerant	R-134a	
HP	¾	
Voltage Rating	Evaporator: 120V (15-amp dedicated circuit required)	Condenser: 208/230-60-1 (15-amp dedicated)
Weight (lbs)	Evaporator: 80	Condenser: 67
Amps (LRA/RLA)	Evaporator: 2/1	Condenser: 35/6.5
dB(A) (Evaporator)	Evaporator: 58.5	
Line Set	Less than 50 ft.: ¾” • More than 50 ft. 7/8”	
Drain Line	¼” ID clear plastic tubing (not provided)	
Installation	Evaporators are installed in the cellar. Condenser is installed up to 100 line ft. away according to the installation instructions found in the technician’s manual. Allow for adequate airflow.	
Thermostat	Remote digital display with 50-ft. cable and 50-ft. bottle probe; 24V thermostat must be purchased separately	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Warranty	Two-year limited warranty (parts and labor)	

* New factory installed Cold Weather Start (-15 F) included.

Optional Accessories

Exterior condenser housing