



### Key Features

- Greater cooling capacity
- Dual evaporators
- No ducting required
- Standard and 24V thermostat options available
- Bottle probe measures liquid temperature
- Flexible installation options
- 55°F temperature differential between cellar environment and condensing unit intake air

### Specifications

| Model                                          | WM900Twin-S                                                                                                                     | WM900Twin-S-24V |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Cellar Size (cu. ft.)                          | 3000*                                                                                                                           |                 |
| BTU/h (w/85°F air entering the condenser coil) | 7850                                                                                                                            |                 |
| CFM                                            | 200 (per unit)                                                                                                                  |                 |
| Dimensions                                     | Evaporator: 16.1"L x 20.5"W x 15.5"H (x2) • Condensing Unit: 24"L x 18.98"W x 16.16"H                                           |                 |
| Refrigerant                                    | R-134a                                                                                                                          |                 |
| Voltage Rating                                 | Evaporator: 115V (15 amp dedicated circuit required) • Condenser: 230V (15 amp dedicated circuit required)                      |                 |
| Weight (lbs)                                   | Evaporators: 60 (per unit) • Condensing Unit: 95                                                                                |                 |
| Amps                                           | Evaporator: 1 running amps (per unit), Compressor: LRA 35 , RLA 6.5                                                             |                 |
| Drain Line                                     | ½" ID clear plastic tubing 'not included'                                                                                       |                 |
| Installation                                   | Evaporator is installed in the cellar. Condensing unit can be installed up to 100 line feet from evaporator unit.               |                 |
| Thermostat                                     | Advanced digital display (50ft. cable), liquid-temperature-measuring bottle probe (retractable cable)                           |                 |
| Temp. Delta                                    | Can maintain a 55°F cellar temperature with up to 110°F condenser air intake temperature                                        |                 |
| Warranty                                       | Two-year limited warranty (parts and labor). <b>Technician MUST return charging records to CellarCool to validate warranty.</b> |                 |

\*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

### Optional Accessories

Exterior condenser housing, 24V thermostat conversion kit, condenser coil coating