



* Front grille and mounting bracket have been painted to match the ceiling

Key Features

- Ready for "Plug-and-Play" installation
- Advanced electronic control system
- 55°F temperature differential
- Front grille and mounting bracket are paintable
- Built-in condensate pump
- Liquid temperature bottle probe
- With remote control

Specifications

Model	CM2500-CR	CM3500-CR	CM5000-CR
Cellar Size (cu. ft.)	500	1000	2000
BTU/h @ 55°F	1540	3650	4450
CFM	107	321	321
Dimensions	22.05"W x 11.08"H x 11.34"D		35.75"W x 14.5"H x 12.75"D
Refrigerant	R-134a	R-134a	R-134a
HP	1/5	1/2	1/2
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)		
Weight (lb.)	40.6	80	80
Amps (Starting/Running)	2 / 1	2 / 1	2 / 1
dBA (Evaporator)	52	58.5	58.5
Line Set	Please refer to the unit's Owner's Manual		
Drainline	1/4" Condensate		
Installation	Evaporator is installed in the cellar, Condenser is installed up to 100 line ft. away with the installation specifications found in the owners manual. Allow for adequate airflow.		
Thermostat	Digital Control Display		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Suggested Condenser	Tecumseh: AEB3417YXASC	Tecumseh: AKA4448YXASC	Tecumseh: AKA4460YXASC
Warranty	2-year parts and labor		

Optional Accessories

Cold Weather Start Kit