



\* Front grille and mounting bracket have been painted to match the ceiling

### Key Features

- Ready for “Plug-and-Play” installation
- Advanced electronic control system
- 55°F temperature differential
- Front grille and mounting bracket are paintable
- Liquid bottle probe & condensate pump included

### Specifications

Model	CM 2500-S	CM 3500-S	CM 5000-S
Cellar Size (cu. ft.)	500	1000	2000
BTU/h @ 55°F	1540	3650	4450
CFM	107	321	321
Dimensions	Evaporator: 22.05”W x 11.08”H x 11.34”D Condenser: 16”W x 10”H x 11.5”D	Evaporator: 35.75”W x 14.5”H x 12.75”D Condenser: 17.25”W x 13”H x 13.5”D	
Refrigerant	R-134a	R-134a	R-134a
HP	1/8	1/2	1/2
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)		
Weight (lb.)	Evaporator: 40.6, Condenser: 33.1	Evaporator: 80, Condenser: 69	Evaporator: 80, Condenser: 69
Amps (Starting/Running)	Evaporator: 2 / 1, Condenser: 11 / 3.81	Evaporator: 1 / 1, Condenser: 48 / 9.5	Evaporator: 1 / 1, Condenser: 48 / 9.5
dBA (Evaporator)	Evaporator: 52, Condenser: 65	Evaporator: 58.5, Condenser: 65	Evaporator: 58.5, Condenser: 65
Line Set	Please refer to the unit Owners Manual		
Drainline	1/4” ID		
Installation	Evaporator is installed in the cellar, Condenser is installed up to 100 line ft. away and with the installation specifications found in the owners manual. Allow for adequate airflow.		
Thermostat	Digital Control Display		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Warranty	2-year parts and labor		

### Optional Accessories

Cold Weather Start Kit