



### Key Features

- Entire unit mounts up to 25 ft. away
- Virtually silent in cellar operation
- Operates in extreme environments
- 55°F temperature differential
- Remote advanced electronic controller w/50 ft. cable
- Includes duct boots on exhaust and supply side
- Liquid temperature bottle probe

### Specifications

Model	Ultimate-FD3300	Ultimate-FD4400	Ultimate-FD8800
Cellar Size (cu. ft.)	800	1250	2000
BTU/h @ 55°F	2688	4200	5760
CFM	256	256	283
Dimensions	14.25"W x 21.75"H x 49.5"D		14.25"W x 28.5"H x 51.5"D
Refrigerant	R-134a	R-134a	R-134a
HP	½	½	½+
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)		
Weight (lb.)	115	115	150
Amps (starting/running)	32 / 9	32 / 9	36 / 10
Ducting Size	8" Supply and Return 8" Exhaust and 8" Intake		8" Supply and 10" Return 8" Exhaust and 10" Intake
Drainline	½" Condensate		
Installation	Within 25 ducted feet of cellar		
Thermostat	Advanced electronic control system		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended		
Warranty	2-year parts and labor		

### Optional Accessories

Ducting plenum, exterior grille