



Key Features

- Great for contractors building custom systems
- Flexible wall mounting coils
- Quiet and efficient in cellar operation
- 55°F temperature differential
- Sleek black power coated finish
- Liquid temperature bottle probe
- With built-in control

Specifications

Model	WM2500-CR	WM3500-CR	WM5000-CR
Cellar Size (cu. ft.)	500	1000	2000
BTU/h @ 55°F	1620	4715	6006
CFM	94	270	278
Dimensions	20"W x 10.5"H x 13"D	20.5"W x 15.5"H x 16.1"D	
Refrigerant	R-134a	R-134a	R-134a
HP	1/5	1/3++	1/2
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)		
Weight (lb.)	25	56	56
Amps (Starting/Running)	2 / 1	2 / 1	2 / 1
dBA (Evaporator)	51	54	54
Line Set	Please refer to the unit Owner's Manual		
Drainline	1/2" Condensate		
Installation	Evaporator coil installed in the cellar		
Thermostat	Optional advanced electronic control system		
Temp. Delta	55°F		
Suggested Condenser	Tecumseh: AEB3417YXASC Copeland: M2FH-0020-IAA-121	Tecumseh: AEA4448YXASC Copeland: M2FH-0049-IAA-201	Tecumseh: AKA4460YXASC
Warranty	2-year parts and labor		

CR — Includes remote control mounted on unit

Optional Accessories

Advanced electronic control system