



Key Features

- Great for contractors building custom systems
- Coils ducted up to 25 feet away
- Virtually silent in cellar operation
- 55°F temperature differential
- Sleek black power coated finish
- Liquid temperature bottle probe
- With remote control

Specifications

Model	FD3500-CR	FD5000-CR
Cellar Size (cu. ft.)	1000	2000
BTU/h @ 55°F	4715	6006
CFM	200	200
Dimensions	23.75"W x 15"H x 22.5"D	
Refrigerant	R-134a	R-134a
HP	½	½+
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)	
Weight (lb.)	57	57
Amps (Starting/Running)	2 / 1	2 / 1
dBA (Evaporator)	54	54
Duct	10" return, 8" supply	
Line Set	Please refer to the unit Owner's Manual	
Drainline	½" Condensate	
Installation	Up to 25 feet away from cellar	
Thermostat	Optional Advanced electronic control system	
Temp. Delta	55°F	
Suggested Condenser	Tecumseh: AEA4448YXASC / Copeland: M2FH-0049-IAA-201	Tecumseh: AKA4460YXASC
Warranty	2-year parts and labor	

CR — Includes remote control

Optional Accessories

Advanced electronic control system, duct kit