



### Key Features

- Ready for “Plug-and-Play” installation
- Coils ducted up to 25 feet away
- Advanced electronic control system
- Sleek black powder coated finish
- 55°F temperature differential
- Liquid temperature bottle probe

### Specifications

Model	FD3500-S	FD5000-S
Cellar Size (cu. ft.)	1000	2000
BTU/h @ 55°F	4715	6006
CFM	200	200
Dimensions	Evaporator: 23.75"W x 15"H x 22.5"D / Condenser: 12"W x 13.5"H x 18"D	
Refrigerant	R-134a	R-134a
HP	½	½+
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)	
Weight (lb.)	Evaporator: 57, Condenser: 66	
Amps (Starting/Running)	Evaporator: 2 / 1, Condenser: 15 / 10	Evaporator: 2 / 1, Condenser: 11 / 4
dBA (Evaporator/Condenser)	54 / 65	54 / 65
Duct	10" return, 8" supply	
Line Set	Please refer to the unit Owner's Manual	
Drainline	½" Condensate	
Installation	Up to 256 ft. away. Follow Owner's Manual specifications	
Thermostat	Advanced electronic control system remote	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Warranty	2-year parts and labor	

### Optional Accessories

Exterior condenser housing, Cold Weather Start Kit