



Key Features

- Greater cooling capacity
- Dual evaporators
- No ducting required
- Standard and 24V thermostat options available
- Liquid-temperature-measuring bottle probe
- Flexible installation
- 55°F temperature differential between cellar environment and condensing unit intake air

Specifications

Model	WM900Twin-S	WM900Twin-S-24V
Cellar Size (cu. ft.)	3000*	
BTUh w/85°F air entering the condenser coil	8500	
CFM	270	
Dimensions	Evaporator: 20.5"W x 15.5"H x 16.1"D (x2)	Condenser: 12"W x 13.5"H x 18"D
Refrigerant	R-404a	
Voltage Rating	Evaporator: 115V (15-amp dedicated circuit required)	Condenser: 208/230-60-1 (15-amp dedicated circuit required)
Weight (lb.)	Evaporator: 57	Condenser: 67
Amps (Starting/Running)	Evaporator: 2 / 1	Condenser: 27/7.3
Drainline	½" ID clear plastic tubing 'not included'	
Installation	Evaporator units are installed in the cellar. Condensing unit is installed outside in a protective enclosure.	
Thermostat	Remote digital display (connected to master), liquid-temperature-measuring bottle probe	
Temp. Delta	55°F temperature differential between cellar environment and condensing unit intake air	
Warranty	Two-year limited warranty (parts and labor)	

*Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

Optional Accessories

Exterior housing, 24V thermostat conversion kit, condenser coil coating