



### Key Features

- This Model is a Ductless Split Only
- Great for contractors building custom systems
- Coil mounted to void corners of racking
- Black exterior to hide unit behind racking
- Extremely quiet in cellar operation
- 55°F temperature differential
- Adjustable fan speed control
- Liquid temperature bottle probe

### Specifications

Model	VM2500-CR	VM3500-CR	VM5000-CR	VM6500-CR
Cellar Size (cu. ft.)	650	1000	1500	2000
BTU/h @ 55°F	3100	3500	≈4100	6500
CFM	214	252	456	456
Dimensions	12"W x 47"H x 12"D			
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	¼	⅓	⅓++	½
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)			
Weight (lb.)	60	60	65	65
Amps (Starting/Running)	1.4 / 1.04	1.4 / 1.14	2.5 / 2	2.5 / 2.1
dBA (Evaporator)	48	56	56	59
Line Set	Please refer to the unit Owner's Manual			
Drainline	½" Condensate			
Installation	Evaporator coil installed in the cellar			
Thermostat	Optional advanced electronic control system			
Temp. Delta	55°F			
Suggested Condenser	Tecumseh: AEA3430YXASC Copeland: M2FH-0026-IAA-072	Tecumseh: AEA4440YXASC Copeland: M2FH-A033-IAA-272	Tecumseh: AEA4448YXASC Copeland: M2FH-0049-IAA-201	Tecumseh: AKA4476YXASC Copeland: M2FH-A056-IAA-272
Warranty	2-year parts and labor			

CR — Includes remote control

### Optional Accessories

Advanced electronic control system

