



* Front grille and mounting bracket have been painted to match the ceiling

Key Features

- Larger cooling capacity
- Dual evaporator
- Ready for “Plug-and-Play” installation
- No ducting required
- Easy accessibility
- Standard and 24V thermostat options available
- Allows for maximum racking space
- Is virtually invisible in the cellar
- Includes a condensate pump system
- Grille of unit comes with a smooth, primed finish
- 55°F temperature differential
- Front grille and mounting bracket are paintable

Specifications

Model	CM9000Twin-S	CM9000Twin-S-24V
Cellar Size (cu. ft.)	Approx. 3000	
BTU/h @ 55°F	8500	
CFM	321	
Dimensions	Evaporator: 12.75”H x 14.5”W x 35.75”D (x2) • W/mounting bracket: 17.10”H x 38.75”D (x2) Condenser: 24”L x 17.5”W x 13.4”H	
Refrigerant	R-404a	
HP	¾	
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)	
Weight (lb.)	Evaporator: 80, Condenser: 67	
Amps (Starting/Running)	Evaporator: 2 / 1, Condenser: 22 / 7.3	
dBA (Evaporator)	Evaporator: 58.5	
Line Set	Please refer to the unit Owners Manual	
Drainline	¼” ID clear plastic tubing (not provided)	
Installation	Evaporator is installed in the cellar, Condenser is installed up to 100 line ft. away and with the installation specifications found in the owners manual. Allow for adequate airflow.	
Thermostat	Remote digital display	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Warranty	2-year parts and labor	

Optional Accessories

Cold Weather Start Kit

