



Key Features

- This Model is a Ductless Split Only
- Ready for “Plug-and-Play” installation
- Adjustable fan speed control
- Flexible wall mount or ceiling joist mount
- Black exterior to hide unit behind a wood grill
- Extremely quiet in cellar operation
- 55°F temperature differential
- Liquid temperature bottle probe

Specifications

| Model | HM2500-S | HM3500-S | HM5000-S | HM6500-S |
|--|--|---|--|---|
| Cellar Size (cu. ft.) | 650 | 1000 | 1500 | 2000 |
| BTU/h @ 55°F | 3100 | 3500 | ≈4100 | 6500 |
| CFM | 214 | 252 | 456 | 456 |
| Dimensions | 47"W x 12"H x 12"D | | | |
| Refrigerant | R-134a | R-134a | R-134a | R-134a |
| HP | ¼ | ½ | ⅓++ | ½ |
| Voltage Rating (20 amp dedicated circuit required) | 115V (230V special order only) | | | |
| Coil Weight (lb.) | 60 | 60 | 65 | 65 |
| Amps (Starting/Running) | Evaporator: 1.4 / 1.04 Condenser: 28 / 5.4 | Evaporator: 1.4 / 1.14 Condenser: 32.7 / 7.2 | Evaporator: 2.5 / 2 Condenser: 40 / 8.2 | Evaporator: 2.5 / 2.1 Condenser: 58.8 / 11.3 |
| dBA (Evaporator) | 48 | 56 | 56 | 59 |
| Line Set | Please refer to the unit Owner's Manual | | | |
| Drainline | ½" Condensate | | | |
| Installation | Evaporator coil installed in the cellar. Condenser up to 100 line feet away. | | | |
| Thermostat | Advanced electronic control system remote | | | |
| Temp. Delta | 55°F | | | |
| Warranty | 2-year parts and labor | | | |

Optional Accessories

Exterior condenser housing

