



### Key Features

- This Model is a Ductless Split Only
- Ready for "Plug-and-Play" installation
- Adjustable fan speed control
- Flexible wall mount or ceiling joist mount
- Black exterior to hide unit behind a wood grill
- Extremely quiet in cellar operation
- 55°F temperature differential
- Liquid temperature bottle probe

### Specifications

Model	HM8200 TWIN-S	HM13000 TWIN-S
Cellar Size (cu. ft.)	3000	4000
BTU/h @ 55°F	8140	13,930
CFM	456 + 456	456 + 456
Units	HM5000 + HM5000	HM6500 + HM6500
Dimensions	47"W x 12"H x 12"D (2 units)	
Refrigerant	R134a	
HP	1/3 + 1/3	1/2 + 1/2
Voltage Rating (20 amp dedicated circuit required)	115V	230V only
Coil Weight (lb.)	60 + 65	65 + 65
Amps (Starting/Running)	2.5 (per Evaporator)	2.5 (per Evaporator)
Line Set	Please refer to the unit Owner's Manual	
Drainline	1/2" Condensate	
Installation	Evaporator coil installed in the cellar. Condenser up to 100 line feet away.	
Thermostat	Advanced electronic control system	
Temp. Delta	55°F	
Warranty	2-year parts and labor	

### Optional Accessories

Exterior condenser housing

