



### Key Features

- This Model is a Ductless Split Only
- Ready for "Plug-and-Play" installation
- Adjustable fan speed control
- Coil mounted in void corners of racking
- Black exterior to hide unit behind racking
- Extremely quiet in cellar operation
- 55°F temperature differential
- Liquid temperature bottle probe

### Specifications

Model	VM2500-S	VM3500-S	VM5000-S	VM6500-S
Cellar Size (cu. ft.)	650	1000	1500	2000
BTU/h @ 55°F	3100	3500	≈4100	6500
CFM	214	252	456	456
Dimensions	12"W x 47"H x 12"D			
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	¼	⅓	⅓++	½
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)			
Coil Weight (lb.)	60	60	65	65
Amps (Starting/Running)	Evaporator: 1.4 / 1.04 Condenser: 28 / 5.4	Evaporator: 1.4 / 1.14 Condenser: 32.7 / 7.2	Evaporator: 2.5 / 2 Condenser: 40 / 8.2	Evaporator: 2.5 / 2.1 Condenser: 58.8 / 11.3
dBA (Evaporator)	48	56	56	59
Line Set	Please refer to the unit Owner's Manual			
Drainline	½" Condensate			
Installation	Evaporator coil installed in the cellar. Condenser up to 100 line feet away.			
Thermostat	Advanced electronic control system remote			
Temp. Delta	55°F			
Warranty	2-year parts and labor			

### Optional Accessories

Exterior condenser housing

