



Key Features

- Ready for “Plug-and-Play” installation
- Flexible wall mounting coils
- Quiet and efficient in cellar operation
- 55°F temperature differential
- Advanced electronic control system
- Liquid temperature bottle probe
- With built-in control

Specifications

Model	WM2500-S	WM3500-S	WM5000-S
Cellar Size (cu. ft.)	500	1000	2000
BTU/h @ 55°F	1620	4715	6006
CFM	94	270	278
Dimensions	Evaporator: 20"W x 10.5"H x 13"D Condenser: 11.5"W x 10.5"H x 14"D	Evaporator: 20.56"W x 15.5"H x 16"D Condenser: 12"W x 13.5"H x 18"D	Evaporator: 20.56"W x 15.5"H x 16"D Condenser: 12"W x 13.5"H x 18"D
Refrigerant	R-134a	R-134a	R-134a
HP	1/8	1/2	1/2+
Voltage Rating (20 amp dedicated circuit required)	115V (230V special order only)		
Weight (lb.)	Evaporator: 25, Condenser: 36	Evaporator: 56, Condenser: 56	Evaporator: 56, Condenser: 66
Amps (Starting/Running)	Evaporator: 2 / 1, Condenser: 11 / 4	Evaporator: 2 / 1, Condenser: 15 / 10	Evaporator: 2 / 1, Condenser: 18 / 9
dBA (Evaporator/Condenser)	51 / 65	54 / 65	54 / 65
Line Set	Please refer to the unit Owner's Manual		
Drainline	1/2" Condensate		
Installation	Evaporator coil installed in the cellar. Condenser up to 100 line feet away. Follow owners manual specifications		
Thermostat	Advanced electronic control system		
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)		
Warranty	2-year parts and labor		

Optional Accessories

Exterior condenser housing, Cold Weather Start Kit

